



Power Flux 10 000 mAh

LCD Display Power Bank

QUICK GUIDE

Power Flux 10 000 mAh

LCD Display Power Bank

Power Delivery architecture.
Up to 20W across 3 devices,
PPS precision and **AFC** technology.



AFC
USB-A1

22,5W
max
IN

PD PPS
USB-C

18W
max
IN

20W
max
OUT

AFC
USB-A2

22,5W
max
OUT

20
WATT

Compatible Devices



MacBook Neo
Single-port charging only



Tablet



Smartphone



TWS

Power Status Display

LCD screen with real-time battery level



Integrated Protection System



Overvoltage
protection



Overheating
protection



Short-circuit
protection

CONTROL BUTTON

TAP x1:
ALWAYS-ON DISPLAY.

TAP x2:
TURN ON/OFF DISPLAY.

LONG PRESS:
LOW-CURRENT MODE ON/OFF

Intelligent Power Distribution

Multi-port output allocation

Two-Ports Charging



15W SHARED
MAX POWER OUTPUT
BASED ON CONNECTED DEVICES DEMAND

Three-Ports Charging



15W SHARED
MAX POWER OUTPUT
BASED ON CONNECTED DEVICES DEMAND



Technology Guide

Charging standards overview

PD

POWER
DELIVERY

Universal fast charging
standard via USB-C.
Delivers higher power
safely and efficiently
across compatible
devices.

PPS

PROGRAMMABLE
POWER SUPPLY

Advanced voltage
regulation protocol.
Optimizes power
output dynamically for
stable and efficient
charging.

AFC

ADAPTIVE
FAST CHARGE

Samsung fast charging
technology.
Adjusts voltage and
current for compatible
devices.

POWER WHAT MATTERS

Power Flux 10 000 mAh

LCD Display Power Bank

Specifications:

USB-C Input: 5,0V DC 3,0A / 9,V DC 2,0A / 12,0V DC 1,5A (18,0W)

USB AFC Output: 5,0V DC 3,0A / 9,0V DC 2,0A / 10,0V DC 2,25A /
12,0V DC 1,5A (AFC 22,5W)

USB-C Output: 5,0V DC 3,0A / 9,0V DC 2,22A / 12,0V DC 1,67A (PD 20,0W)

Total Output: 22,5W max

Li-Pol Battery: 10.000 mAh (3,85V 38,5Wh)

Recharging cable:

Connector 1/2: USB-C

uniquo-tech.com

SBS spa
Via Circonvallazione s/n
28010 Miasino (No) Italy



REV1_05_26

Follow us on: 
customercare@uniquo-tech.com