



Power Flux 10 000 mAh

Slim Power Bank

QUICK GUIDE



ULTRA
SLIM

Power Flux 10 000 mAh

Slim Power Bank

Power Delivery architecture.
Up to 20W across 2 devices,
PPS precision and **AFC** technology.



PD PPS
USB-C

18W
max
IN 20W
max
OUT

AFC
USB-A

22,5W
max
OUT

20
WATT

Compatible Devices



MacBook Neo
Single-port charging only



Tablet



Smartphone



TWS

Power Status Led

Real-time battery level indication



REMAINING
BATTERY

CONTROL
BUTTON

TAP x1:
TURN LED ON.
TAP x2:
QUICK LED ON.

Integrated Protection System



Overvoltage
protection



Overheating
protection




Short-circuit
protection

Intelligent Power Distribution

Multi-port output allocation


Single-Port Charging



Two-Ports Charging



15W SHARED
MAX POWER OUTPUT
BASED ON CONNECTED DEVICES DEMAND



Technology Guide

Charging standards overview

PD

POWER
DELIVERY

Universal fast charging
standard via USB-C.
Delivers higher power
safely and efficiently
across compatible
devices.

PPS

PROGRAMMABLE
POWER SUPPLY

Advanced voltage
regulation protocol.
Optimizes power
output dynamically for
stable and efficient
charging.

AFC

ADAPTIVE
FAST CHARGE

Samsung fast charging
technology.
Adjusts voltage and
current for compatible
devices.

POWER WHAT MATTERS

Power Flux 10 000 mAh

Slim Power Bank

Specifications:

USB-C Input: 5,0V DC 3,0A / 9,V DC 2,0A / 12,0V DC 1,5A (18,0W)

USB AFC Output: 5,0V DC 3,0A / 9,0V DC 2,0A / 10,0V DC 2,25A /
12,0V DC 1,5A (AFC 22,5W)

USB-C Output: 5,0V DC 3,0A / 9,0V DC 2,22A / 12,0V DC 1,67A (PD 20,0W)

Total Output: 22,5W max

Li-Pol Battery: 10.000 mAh (3,85V 38,5Wh)

Recharging cable:

Connector 1/2: USB-C

uniquo-tech.com

SBS spa
Via Circonvallazione s/n
28010 Miasino (No) Italy



REV1_04_26

Follow us on: 
customercare@uniquo-tech.com