



Mini Cube 30 watt

Wall Charger

QUICK GUIDE

Mini Cube 30

Wall Charger

Power Delivery architecture.
Up to 30W output,
PPS precision and **GaN** efficiency.



Premium cable
USB-C to USB-C
included

1,5m
LENGTH

PD

PPS

30W max
OUTPUT

30
WATT

Compatible
devices



MacBook Neo / Air



Tablet



Smartphone



TWS

Technology Guide

Charging standards overview

PD

POWER
DELIVERY

Universal fast charging
standard via USB-C.
Delivers higher power
safely and efficiently
across compatible
devices.

PPS

PROGRAMMABLE
POWER SUPPLY

Advanced voltage
regulation protocol.
Optimizes power
output dynamically for
stable and efficient
charging.

Integrated Protection System



Overvoltage
protection



Overheating
protection



Short-circuit
protection

POWER WHAT MATTERS

Mini Cube 30 watt

Wall Charger

Specifications:

Input: 100-240 V AC 50/60 Hz 0,8 A Max

USB-C Output: 5,0 V DC 3,0 A / 9,0 V DC 3,0 A / 12,0 V DC 2,5 A /
15,0 V DC 2,0 A / 20,0 V DC 1,5 A (PD 30,0 W)

3,0 A Cable:

Connector 1/2: USB-C 2.0

Cable length: 150 cm / 5 ft

uniquo-tech.com


SBS spa

Via Circonvallazione s/n
28010 Miasino (No) Italy



**GALLIUM NITRIDE
TECHNOLOGY**

High-efficiency
semiconductor material.
Allows compact design
with improved power
performance.



REV1_05_26

Follow us on:

customercare@uniquo-tech.com