



Control Cube 100 watt

TFT Display Wall Charger

QUICK GUIDE

Control Cube 100

TFT Display Wall Charger

Intelligent power distribution.
Up to 100W across 4 devices,
PPS precision and **GaN** efficiency.

Premium cable
USB-C to USB-C
included

1,5m
LENGTH



PD PPS
USB-C 1/2 USB-C 3
100W max 20W max
OUT OUT

AFC
USB-A
18W max
OUT

100
WATT

Compatible
devices



Laptop



Tablet



Smartphone



TWS

Active Matrix Display

TFT screen with real-time views

DISPLAY INTERFACE
OVERALL OUTPUT
POWER OVERVIEW
TEMPERATURE STATUS
CHARGING TIME



TOUCH CONTROL
BUTTON

TAP x1:
SWITCH VIEWS
PRESS 2s:
TURN DISPLAY

90° DISPLAY
ROTATION
FOR HORIZONTAL
AND VERTICAL
SOCKETS



AUTOMATIC
STANDBY MODE
WHEN NO DEVICE
IS CONNECTED



Intelligent Power Distribution

Multi-port output allocation

Two-Ports Charging



Three-Ports Charging



Four-Ports Charging



15W SHARED
MAX POWER
OUTPUT
BASED ON CONNECTED
DEVICES DEMAND

Technology Guide

Charging standards overview

PD

POWER
DELIVERY

Universal fast charging standard via USB-C. Delivers higher power safely and efficiently across compatible devices.

PPS

PROGRAMMABLE
POWER SUPPLY

Advanced voltage regulation protocol. Optimizes power output dynamically for stable and efficient charging.

AFC

ADAPTIVE
FAST CHARGE

Samsung fast charging technology. Adjusts voltage and current for compatible devices.

Integrated Protection System



Overvoltage
protection



Overheating
protection



Short-circuit
protection

POWER WHAT MATTERS

Control Cube 100 watt

TFT Display Wall Charger

Specifications:

Input: 100-240V AC 50/60HZ 1,5 A Max

USB-C1 Output: 5,0 V DC 3,0 A / 9,0 V DC 3,0 A / 12,0 V DC 3,0 A / 15,0 V DC 3,0 A / 20,0 V DC 5,0 A (PD 100,0 W)

USB-C2 Output: 5,0 V DC 3,0 A / 9,0 V DC 3,0 A / 12,0 V DC 3,0 A / 15,0 V DC 3,0 A / 20,0 V DC 5,0 A (PD 100,0 W)

USB-C3 Output: 5,0 V DC 3,0 A / 9,0 V DC 2,22 A / 12,0 V DC 1,6 A (PD 20,0 W)

USB-A Output: 5,0 V DC 3,0 A / 9,0 V DC 2,0 A / 12,0 V DC 1,5 A (AFC 18,0W)

USB-C1 + USB-C2 Output: 65,0 W + 35,0 W

USB-C1 + USB-C3 Output: 65,0 W + 20,0 W

USB-C1 + USB-A Output: 65,0 W + 18,0 W

USB-C2 + USB-C3 Output: 65,0 W + 20,0 W

USB-C2 + USB-A Output: 65,0 W + 18,0 W

USB-C3 + USB-A Output: 5,0 V DC 3,0 A (15 W max)

USB-C1 + USB-C2 + USB-C3 Output: 45,0 W + 35,0 W + 20,0 W

USB-C1 + USB-C2 + USB-A Output: 45,0 W + 35,0 W + 18,0 W

USB-C1 / USB-C2 + (USB-C3 + USB-A) Output: 45,0 W + 35,0 W + 5,0 V DC 3,0 A (15 W max)

Total Output: 100,0 W max

5,0 A Cable:

Connector 1/2: USB-C 2.0

Cable length: 150 cm / 5 ft

uniquo-tech.com

SBS spa

Via Circonvallazione s/n


28010 Miasino (No) Italy



**GALLIUM NITRIDE
TECHNOLOGY**

High-efficiency
semiconductor material.

Allows compact design
with improved power
performance.



Follow us on:

customercare@uniquo-tech.com