



Control Cube 70 watt

TFT Display Wall Charger

QUICK GUIDE

Control Cube 70

TFT Display Wall Charger

Intelligent power distribution.

Up to 70W across 3 devices,
PPS precision and **GaN** efficiency.

Premium cable
USB-C to USB-C
included

1,5m
LENGTH



PD PPS
USB-C 1/2

70W
max
OUT

AFC
USB-A

30W
max
OUT

70
WATT

Compatible
devices



Laptop



Tablet



Smartphone




TWS

Active Matrix Display

TFT screen with real-time views

DISPLAY INTERFACE

OVERALL OUTPUT
POWER OVERVIEW
TEMPERATURE STATUS
CHARGING TIME



TOUCH CONTROL
BUTTON

TAP x1:
SWITCH VIEWS
PRESS 2s:
TURN DISPLAY

90° DISPLAY
ROTATION
FOR HORIZONTAL
AND VERTICAL
SOCKETS




AUTOMATIC
STANDBY MODE
WHEN NO DEVICE
IS CONNECTED



Intelligent Power Distribution

Multi-port output allocation

Two-Ports Charging



Three-Ports Charging



15W SHARED
MAX POWER OUTPUT
BASED ON CONNECTED
DEVICES DEMAND

Technology Guide

Charging standards overview

PD

POWER
DELIVERY

Universal fast charging standard via USB-C. Delivers higher power safely and efficiently across compatible devices.

PPS

PROGRAMMABLE
POWER SUPPLY

Advanced voltage regulation protocol. Optimizes power output dynamically for stable and efficient charging.

AFC

ADAPTIVE
FAST CHARGE

Samsung fast charging technology. Adjusts voltage and current for compatible devices.

Integrated Protection System



Overvoltage
protection



Overheating
protection



Short-circuit
protection

POWER WHAT MATTERS

Control Cube 70 watt

TFT Display Wall Charger

Specifications:

Input: 100-240V AC 50/60HZ 1,5 A Max

USB-C1 Output: 5,0 V DC 3,0 A / 9,0 V DC 3,0 A / 12,0 V DC 3,0 A /
15,0 V DC 3,0 A / 20,0 V DC 3,5 A (PD 70,0 W)

USB-C2 Output: 5,0 V DC 3,0 A / 9,0 V DC 3,0 A / 12,0 V DC 3,0 A /
15,0 V DC 3,0 A / 20,0 V DC 3,5 A (PD 70,0 W)

USB-A Output: 5,0 V DC 3,0 A / 9,0 V DC 3,0 A / 12,0 V DC 2,5 A /
20,0 V DC 1,5 A (AFC 30,0W)

USB-C1 + USB-C2 Output: 45,0 W + 20,0 W

USB-C1 + USB-A Output: 45,0 W + 18,0 W

USB-C2 + USB-A Output: 5,0 V DC 3,0 A (15 W max)

USB-C1 + USB-C2 + USB-A Output: 45,0 W + 5,0 V DC 3,0 A (15 W max)

Total Output: 70,0 W max

3,0 A Cable:

Connector 1/2: USB-C 2.0

Cable length: 150 cm / 5 ft

uniquo-tech.com

SBS spa

Via Circonvallazione s/n


28010 Miasino (No) Italy



**GALLIUM NITRIDE
TECHNOLOGY**

High-efficiency
semiconductor material.

Allows compact design
with improved power
performance.



REV1_05_26

Follow us on:

customercare@uniquo-tech.com